

Product Name: 14" Track 2" Legs
Description: 1400T200-54

Physical Properties

Web Depth (in)	14.00	Gauge	16
Leg Length (in)	2.000	Mils	54
Standard Coating	CP60	Design Thickness (in)	0.0566
Available Coating *	CP90	Minimum Thickness (in)	0.0538
Weight (lb/ft)	3.460	Yield Stress Fy (ksi)	50
		Ultimate, Fu (ksi)	65

Section Properties

Cross Sectional Area (A)	1.018 in ²
Moment of Inertia (Ix)	24.221 in ⁴
Radius of Gyration (Rx)	4.878 in
Gross Moment of Inertia (Iy)	0.242 in ⁴
Gross Radius of Gyration (Ry)	0.487 in

Effective Section Properties


Moment of Inertia for Deflection (Ixe)	18.389 in ⁴
Section Modulus (Sxe)	1.589 in ³
Allowable Bending Moment (Ma)	47.56 in-k

Torsional Properties

St. Venant Torsion Constant (Jx1000)	1.087 in ⁴
Warping Constant (Cw)	9.520 in ⁶
Distance from Shear Center to Neutral Axis (Xo)	-0.665 in
Radii of Gyration (Ro)	4.947 in
Torsional Flexural Constant (Beta)	0.989

Web-depth to thickness ratio exceeds 200. Web Stiffeners are required at all support points and concentrated loads.

*By request



MANUFACTURING Codes & Standards

NASPEC AISI S100-07 IBC 2009 2012 Compliant
Coated in accordance to ASTM A1003 & A653
Meets or exceeds ASTM C955 & AISI S200
Code Evaluation Report ICC-ESR #3957

GREEN Benefits & LEED Data:

LEED Credit MR 2 - Construction Waste Mgmt - 1-2 Points
LEED Credit MR 4 - Recycled Credit - 1-2 Points
LEED Credit MR 5 - Regional Materials - 1-2 Points
CRACO products are 100% recyclable
Contact Technical Services for more information