

Product Name: 2-1/2" SmartTrack 30mil 2" Legs
Description: 250ST200-30

Physical Properties

Web Depth (in)	2.50	Yield Stress Fy (KSI)	33
Leg Length (in)	2.00	Mils	30
Standard Coating	G40	Design Thickness (in)	0.0312
Weight (lb/ft)	0.690	Minimum Thickness (in)	0.0296
		Gauge	20

Section Properties


Cross Sectional Area (A)	0.203 in ²
Moment of Inertia (Ix)	0.255 in ⁴
Radius of Gyration (Rx)	1.119 in
Gross Moment of Inertia (Iy)	0.088 in ⁴
Gross Radius of Gyration (Ry)	0.658 in

Effective Section Properties

Moment of Inertia for Deflection (Ixe)	0.173 in ⁴
Section Modulus (Sxe)	0.097 in ³
Allowable Bending Moment (Ma)	1.940 in-k

Torsional Properties

St. Venant Torsion Constant (Jx1000)	0.0659 in ⁴
Warping Constant (Cw)	0.108 in ⁶
Distance from Shear Center to Neutral Axis (Xo)	-1.420 in
Radii of Gyration (Ro)	1.920 in
Torsional Flexural Constant (Beta)	0.457



MANUFACTURING Codes & Standards

- NASPEC AISI S100-07 IBC 2009 2012 Compliant
- Coated in accordance to ASTM A1003 & A653
- Meets or exceeds ASTM C645 & C745 & AISI S220
- Multiple UL Design Listings including U419
- 3rd Party Code Evaluation Report ICC-ESR #3943
- US Patent No. D618,365S

GREEN Benefits & LEED Data:

- LEED Credit MR 2 - Construction Waste Mgmt - 1-2 Points
- LEED Credit MR 4 - Recycled Credit - 1-2 Points
- LEED Credit MR 5 - Regional Materials - 1-2 Points
- CRACO products are 100% recyclable
- Contact Technical Services for more information