

Product Name: 2-1/2" Stud
Description: 250S250-43

Physical Properties

Web Depth (in)	2.500	Gauge	20
Flange Width (in)	2.500	Mils	43
Return Lip (in)	0.625	Design Thickness (in)	0.0451
Standard Coating	CP60	Minimum Thickness (in)	0.0428
Available Coating *	CP90	Yield Stress Fy (ksi)	33
Weight (lb/ft)	1.290	Ultimate, Fu (ksi)	45

Section Properties

Cross Sectional Area (A)	0.379 in ²
Moment of Inertia (Ix)	0.426 in ⁴
Radius of Gyration (Rx)	1.060 in
Gross Moment of Inertia (Iy)	0.336 in ⁴
Gross Radius of Gyration (Ry)	0.941 in

Effective Section Properties

Moment of Inertia for Deflection (Ixe)	0.426 in ⁴
Section Modulus (Sxe)	0.292 in ³
Allowable Bending Moment (Ma)	6.160 in-k

Torsional Properties

St. Venant Torsion Constant (Jx1000)	0.257 in ⁴
Warping Constant (Cw)	0.638 in ⁶
Distance from Shear Center to Neutral Axis (Xo)	-2.404 in
Radii of Gyration (Ro)	2.791 in
Torsional Flexural Constant (Beta)	0.258

*By request



MANUFACTURING Codes & Standards

NASPEC AISI S100-07 IBC 2009 2012 Compliant
Coated in accordance to ASTM A1003 & A653
Meets or exceeds ASTM C955 & AISI S200
Code Evaluation Report ICC-ESR #3957

GREEN Benefits & LEED Data:

LEED Credit MR 2 - Construction Waste Mgmt - 1-2 Points
LEED Credit MR 4 - Recycled Credit - 1-2 Points
LEED Credit MR 5 - Regional Materials - 1-2 Points
CRACO products are 100% recyclable
Contact Technical Services for more information