

Product Name: 2-1/2" Stud
Description: 250S250-68

Physical Properties

Web Depth (in)	2.500	Gauge	14
Flange Width (in)	2.500	Mils	68
Return Lip (in)	0.625	Design Thickness (in)	0.0713
Standard Coating	CP60	Minimum Thickness (in)	0.0677
Available Coating *	CP90	Yield Stress Fy (ksi)	50
Weight (lb/ft)	1.990	Ultimate, Fu (ksi)	65

Section Properties

Cross Sectional Area (A)	0.586 in ²
Moment of Inertia (Ix)	0.643 in ⁴
Radius of Gyration (Rx)	1.047 in
Gross Moment of Inertia (Iy)	0.503 in ⁴
Gross Radius of Gyration (Ry)	0.926 in

Effective Section Properties

Moment of Inertia for Deflection (Ixe)	0.643 in ⁴
Section Modulus (Sxe)	0.446 in ³
Allowable Bending Moment (Ma)	13.36 in-k

Torsional Properties

St. Venant Torsion Constant (Jx1000)	0.993 in ⁴
Warping Constant (Cw)	0.944 in ⁶
Distance from Shear Center to Neutral Axis (Xo)	-2.371 in
Radii of Gyration (Ro)	2.752 in
Torsional Flexural Constant (Beta)	0.258

*By request



MANUFACTURING Codes & Standards

NASPEC AISI S100-07 IBC 2009 2012 Compliant
Coated in accordance to ASTM A1003 & A653
Meets or exceeds ASTM C955 & AISI S200
Code Evaluation Report ICC-ESR #3957

GREEN Benefits & LEED Data:

LEED Credit MR 2 - Construction Waste Mgmt - 1-2 Points
LEED Credit MR 4 - Recycled Credit - 1-2 Points
LEED Credit MR 5 - Regional Materials - 1-2 Points
CRACO products are 100% recyclable
Contact Technical Services for more information