

Product Name: 6" Stud
Description: 600S137-97

Physical Properties

Web Depth (in)	6.000	Gauge	12
Flange Width (in)	1.375	Mils	97
Return Lip (in)	0.375	Design Thickness (in)	0.1017
Standard Coating	CP60	Minimum Thickness (in)	0.0966
Available Coating *	CP90	Yield Stress Fy (ksi)	50
Weight (lb/ft)	3.030	Ultimate, Fu (ksi)	65

Section Properties

Cross Sectional Area (A)	0.889 in ²
Moment of Inertia (Ix)	4.188 in ⁴
Radius of Gyration (Rx)	2.170 in
Gross Moment of Inertia (Iy)	0.159 in ⁴
Gross Radius of Gyration (Ry)	0.422 in

Effective Section Properties

Moment of Inertia for Deflection (Ixe)	4.188 in ⁴
Section Modulus (Sxe)	1.396 in ³
Allowable Bending Moment (Ma)	50.80 in-k

Torsional Properties

St. Venant Torsion Constant (Jx1000)	3.066 in ⁴
Warping Constant (Cw)	1.216 in ⁶
Distance from Shear Center to Neutral Axis (Xo)	-0.734 in
Radii of Gyration (Ro)	2.330 in
Torsional Flexural Constant (Beta)	0.901

*By request



MANUFACTURING Codes & Standards

NASPEC AISI S100-07 IBC 2009 2012 Compliant
Coated in accordance to ASTM A1003 & A653
Meets or exceeds ASTM C955 & AISI S200
Code Evaluation Report ICC-ESR #3957

GREEN Benefits & LEED Data:

LEED Credit MR 2 - Construction Waste Mgmt - 1-2 Points
LEED Credit MR 4 - Recycled Credit - 1-2 Points
LEED Credit MR 5 - Regional Materials - 1-2 Points
CRACO products are 100% recyclable
Contact Technical Services for more information