

Product Name: 6" Stud
Description: 600S162-33

Physical Properties

Web Depth (in)	6.000	Gauge	20
Flange Width (in)	1.625	Mils	33
Return Lip (in)	0.500	Design Thickness (in)	0.0346
Standard Coating	CP60	Minimum Thickness (in)	0.0329
Available Coating *	CP90	Yield Stress Fy (ksi)	33
Weight (lb/ft)	1.170	Ultimate, Fu (ksi)	45

Section Properties

Cross Sectional Area (A)	0.344 in ²
Moment of Inertia (Ix)	1.793 in ⁴
Radius of Gyration (Rx)	2.282 in
Gross Moment of Inertia (Iy)	0.116 in ⁴
Gross Radius of Gyration (Ry)	0.581 in

Effective Section Properties

Moment of Inertia for Deflection (Ixe)	1.793 in ⁴
Section Modulus (Sxe)	0.577 in ³
Allowable Bending Moment (Ma)	11.41 in-k

Torsional Properties

St. Venant Torsion Constant (Jx1000)	0.137 in ⁴
Warping Constant (Cw)	0.861 in ⁶
Distance from Shear Center to Neutral Axis (Xo)	-1.072 in
Radii of Gyration (Ro)	2.587 in
Torsional Flexural Constant (Beta)	0.828

*By request



MANUFACTURING Codes & Standards

NASPEC AISI S100-07 IBC 2009 2012 Compliant
Coated in accordance to ASTM A1003 & A653
Meets or exceeds ASTM C955 & AISI S200
Code Evaluation Report ICC-ESR #3957

GREEN Benefits & LEED Data:

LEED Credit MR 2 - Construction Waste Mgmt - 1-2 Points
LEED Credit MR 4 - Recycled Credit - 1-2 Points
LEED Credit MR 5 - Regional Materials - 1-2 Points
CRACO products are 100% recyclable
Contact Technical Services for more information