

Product Name: 8" Stud
Description: 800S162-54

Physical Properties

Web Depth (in)	8.000	Gauge	16
Flange Width (in)	1.625	Mils	54
Return Lip (in)	0.500	Design Thickness (in)	0.0566
Standard Coating	CP60	Minimum Thickness (in)	0.0538
Available Coating *	CP90	Yield Stress Fy (ksi)	50
Weight (lb/ft)	2.280	Ultimate, Fu (ksi)	65

Section Properties

Cross Sectional Area (A)	0.670 in ²
Moment of Inertia (Ix)	5.736 in ⁴
Radius of Gyration (Rx)	2.927 in
Gross Moment of Inertia (Iy)	0.194 in ⁴
Gross Radius of Gyration (Ry)	0.539 in

Effective Section Properties

Moment of Inertia for Deflection (Ixe)	5.600 in ⁴
Section Modulus (Sxe)	1.229 in ³
Allowable Bending Moment (Ma)	36.79 in-k

Torsional Properties

St. Venant Torsion Constant (Jx1000)	0.715 in ⁴
Warping Constant (Cw)	2.539 in ⁶
Distance from Shear Center to Neutral Axis (Xo)	-0.914 in
Radii of Gyration (Ro)	3.113 in
Torsional Flexural Constant (Beta)	0.914

*By request



MANUFACTURING Codes & Standards

NASPEC AISI S100-07 IBC 2009 2012 Compliant
Coated in accordance to ASTM A1003 & A653
Meets or exceeds ASTM C955 & AISI S200
Code Evaluation Report ICC-ESR #3957

GREEN Benefits & LEED Data:

LEED Credit MR 2 - Construction Waste Mgmt - 1-2 Points
LEED Credit MR 4 - Recycled Credit - 1-2 Points
LEED Credit MR 5 - Regional Materials - 1-2 Points
CRACO products are 100% recyclable
Contact Technical Services for more information